

W.I.C.C. Ltd
119 MULLER RD
PO Box 252
WASHINGTON IL 61571
(309)-444-4125
FAX (309)-444-3313


CURRENT TRANSFORMER MODEL 617

6.50" I.D.


PAGE No 1-46

REV 18DEC00

TERMINAL OPTION



LEAD WIRE OPTION



NOTES

- 1). ALL DIMENSIONS IN INCHES
- 2). ALL DIMENSIONS REF ONLY

Specifications

- ☐ Secondary sources 5 amps AC at rated F.S. primary current
- ☐ Nominal operating frequency range is 50-400HZ
- ☐ Thermal rating factor is 2.00 @ 30C for ratios up to 1500:5A, 1.50 @ 30C for ratios of 1500:5A up to 2000:5A, and 1.33 @ 30C for ratios above 2000:5A
- ☐ Insulation voltage class is 0.6KV BIL 10KV
- ☐ For indoor applications only
- ☐ Reference documents IEEE C57.13, UL1244, CSA CAN3-C13-M83, and IEC 44-1
- ☐ Enclosure is multi-layer tape buildup with heavy vinyl finish, color is black
- ☐ Optional bracket is aluminum, optional plate is XX phenolic

Options, contact Factory for information


- ☐ Medium voltage insulation classes (lead wires only, physical size increases)
- ☐ 1, 0.2, and 0.1 A output at F.S. primary amperage. Other non-standard ratings also available
- ☐ 8-32 Screw Terminals or #14 AWG UL 1015 Lead Wires
- ☐ Custom lead wire lengths and types
- ☐ Thermal ratings above 2.00 for selected ratios
- ☐ Center tap and custom multi tap winding arrangements

6.50" I.D.

PAGE No 1-47


REV 18DEC00

CURRENT TRANSFORMER MODEL 617



W.I.C.C. Ltd
119 MULLER RD
PO Box 252
WASHINGTON IL 61571
(309)-444-4125
FAX (309)-444-3313

TYPICAL EXCITATION CURVE for WICC MODEL 617 at 60HZ



W.I.C.C. PART NUMBER *	RATIO	ANSI ACCURACY CLASS @ 60HZ					RELAY CLASS	NOMINAL WINDING RESISTANCE (ohm)
		B0.1	B0.2	B0.5	B0.9	B1.8		
617-100-00-xxx	100:5A	1.2	-	-	-	-	C10	0.03
617-150-00-xxx	150:5A	1.2	1.2	-	-	-	C10	0.05
617-200-00-xxx	200:5A	0.6	0.6	1.2	-	-	C20	0.07
617-300-00-xxx	300:5A	0.3	0.3	0.6	1.2	-	C20	0.10
617-400-00-xxx	400:5A	0.3	0.3	0.6	0.6	1.2	C50	0.13
617-600-00-xxx	600:5A	0.3	0.3	0.3	0.3	0.6	C50	0.20
617-800-00-xxx	800:5A	0.3	0.3	0.3	0.3	0.3	C100	0.27
617-1000-00-xxx	1000:5A	0.3	0.3	0.3	0.3	0.3	C100	0.33
617-1200-00-xxx	1200:5A	0.3	0.3	0.3	0.3	0.3	C100	0.39
617-1600-00-xxx	1600:5A	0.3	0.3	0.3	0.3	0.3	C200	0.65
617-2000-00-xxx	2000:5A	0.3	0.3	0.3	0.3	0.3	C200	1.3
617-3000-00-xxx	3000:5A	0.3	0.3	0.3	0.3	0.3	C200	2.0
617-4000-00-xxx	4000:5A	0.3	0.3	0.3	0.3	0.3	C400	2.6

* "xxx" describes termination: "T" FOR BRASS SCREW TERMINALS and "Lyyy" FOR LEAD WIRES (Where "yyy" is the lead length in inches. For example, "L24" represents 24 inch long lead wires.)